

# **EVERPURE®** CLARIS FLOWMETER EV4339-31

MONITORING SYSTEM FOR CLARIS FILTER CARTRIDGE SYSTEMS

Claris Flowmeter: EV4339-31



### **APPLICATIONS**

Vending

Hotel

Restaurant

Cafe

### **FEATURES • BENEFITS**

The programming and display unit provides the following information:

- Residual capacity of installed filter cartridge
- Filtrate volume of the last five installed filter cartridges
- Operation time of the last five installed filter cartridges
- Total filtrate volume since Flow Sensor installation

The CLARIS Flow Sensor has been developed specifically to monitor the usage rate of the CLARIS water filter system and to determine the optimum cartridge replacement interval. After setting the programming unit to monitor the specific filter size, the Claris Flow Sensor continually measures the filtrate volume to calculate and display the remaining filtration capcity in liters. Once the available filtration capacity is exhausted or the maximum operation time has been reached the display unit indicates the filter cartridge replacement

### **INSTALLATION TIPS**

If mounting display to a wall, securely connect the display to the wall using suitable screws or mounting hardware

Shutoff valve must be installed upstream of the filter

Refer to Installation, Operation & Maintenance manual for flowmeter start up and programing

## **OPERATION TIPS**

Change Claris cartridge when its pre-calculated water volume has been reached or at least once per year

Change cartridges when capacity is reached

### SIZING

Operating pressure: 29 - 116 psi (2 - 8 bar)

Flow rate: 2.64 - 26.4 gph (10 - 100 Lph)

## **EVERPURE** CLARIS FLOWMETER

FV4339-31



### **SPECIFICATIONS**

### **SENSOR UNIT**

**Overall Dimensions** 3.15" H x 1.81" W x 1.69" D (8 x 4.5 x 4.2 cm)

### Inlet Connection 3/8" BSP F Nut

## Outlet Connection

3/8" BSP M

## Operating Pressure

29 - 116 psi (2 - 8 bar)

#### Flow Rate

2.64 - 26.4 gph (10 - 100 Lph)

# Pressure Loss up to 26.4 gph (100 Lph) flow rate

3 psi (0.2 bar)

## Precision (horizontal installation)

±5%

### Water Temperature

39 - 86°F (4 - 30°C)

### **Ambient Temperature**

39 - 104°F (4 - 40°C)

### **Installation Position**

Horizontal recommended

### PROGRAMMING AND DISPLAY UNIT

### Overall Dimensions

1.97" H x 2.95" W x 67" L (5 x 7.4 x 170.1cm)

### Splash Proof

IPX4

### **Display 5 Digits**

Counter 99999 - 9999 gallons (Downwards 99999 - 9999 L)

#### Cable

59" (1.5 meters)

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

### **WARRANTY**

Everpure Claris water treatment systems by Pentair® are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



### FILTRATION & PROCESSING SOLUTIONS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM 800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC, 3175, AUSTRALIA 1300.576.190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA

86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301

91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

**EVERPURE-SHURFLO EUROPE**, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM +32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN 81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA,390 HAVELOCK ROAD, #04-01, KING'S CENTRE, SINGAPORE 169662 65.6795.2213 TEL • FAX: 65.6795.2219 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2014 Pentair Filtration Solutions, LLC EV4339-31 MR14