



900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-05 L

DIMENSIONS

| | | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|---------------|
| Length | mm | 425,00 | 510,00 |
| Depth | mm | 900,00 | 990,00 |
| Height | mm | 320,00 | 590,00 |
| Weigth | Kg | 70,00 | 80,00 |
| Volumen | m3 | 0,12 | 0,30 |

ELECTRICITY

| | | | |
|----------|--|--|-------------|
| Not used | | | 0,00 |
|----------|--|--|-------------|

WATER

Not used

GAS

| | | |
|-------------|--------------------|-----------------|
| Power | KW | 9,34 |
| | Kcal/h | 8.032,40 |
| LPG | Consumption (kg/h) | 0,74 |
| | Pressure (g/cm2) | 37,00 |
| Natural Gas | Consumption (m3/h) | 0,95 |
| | Pressure (g/cm2) | 18,00 |

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-05 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Smooth hot-plate. Surface area: 24 dm².

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

| Connections points | X | Y | Z | Diameter | Information |
|---------------------------|----------|----------|----------|-----------------|--|
| GAS | 365 | 738 | 147 | R.3/4"G | Prever regulador y llave de corte individual |

