



LEVEL SOUND

Tumble Dryers

Tumble Dryers Green Evolution

TUMBLE DRYER, SR-11 E

DIMENSIONS		<u>Article</u>	<u>Packed</u>	TUMBLE DRYER, SR-11 E GREEN EVOLUTION Load Capacity: 12 kg. (load factor 1:18) or 10 kg (load factor 1:22).
Length	mm	785,00	880,00	Production: ÷ 21 kg/h.
ū		840,00	955,00	External case made of skin plate, grey color, with stainless steel aesthetics.
Depth	mm	,	,	Axial-radial airflow gives low energy consumption and a bigger drying
Height	mm	1.694,00	1.840,00	efficiency.
Weigth	Kg	170,00	200,00	Time selector.
Volumen	m3		1,55	Temperature selector. COOL DOWN at end of cycle.
				Push -Pull button to START/STOP.
ELECTRICITY				Lamp indicator ON and HEATING.
Electric power		KW	12,55	Open door with safety device.
230V -1+N			NO	EMERGENCY stop button.
230V - III			3x6+T - 50 A	Frecuency speed variator.
			4x4+T - 25 A	Alarm noise indicator at end of cycle.
400V - III+N			4X4+1 - 25 A	Air extraction volume: 870 m3/h.
WATED				IMPORTANT: Stainless steel drum.
WATER				IMPORTANT: Reversing drum .
Not used				Drum diameter: 750 mm
				Depth of drum: 475 mm Drum volume: 210 litres.
				Diameter of door: 574 mm.
<u>GAS</u>				reversible door hanging.
Not used				Fluff filter in lower part .
				Transmission by means of motoreducer.
				Main heating system: electric.
				Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.
				Heating power: 12 kW.
				Total power: 12,55 kW.
				Dimensions: 785 x 840 x 1.694 mm
				OPTIONS:
				- Door with double glass
<u>STEAM</u>		Not used		- External case in stainless steel
				- Front panel in stainless steel
				- Marine version for ships (440 V III)
AID		Not used		
<u>AIR</u>		Not usea		

Connections points	x	Υ	Z	Diameter	Information
ELECTRICITY	528	0	821		0
EXHAUST	558	0	169	200 mm.	

64,00

(dB)

