



Catalogue :

OTHER REFRIGERATION

Chapter :

DISPLAY TRAYS

Article :

VTP-139 RP Remote Flat Negro 230V 1N 50H

Code:

19005240

<u>DIMENSIONS AND WEIGHTS</u>		<u>Net dimensions</u>	<u>Packed</u>
Length	mm	1.380,00	480,00
Depth	mm	415,00	1.940,00
Height	mm	278,00	530,00
Weight	kg	49,00	51,00
Volume	m3	0,16	0,49
<u>ELECTRICITY</u>		230V	50Hz
	Power		0,18 kW
Connections	230 V. 1+N+T	2X1,5+T - 2 A	
	230 V. III+T	3X4+T - 40 A	
	400 V. III+N+T	4X2,5+T - 32 A	
<u>GAS</u>	Not necessary		
<u>WATER</u>	Not necessary		
<u>STEAM</u>	Not necessary		
<u>AIR</u>	Not necessary		
			R-134a
	Refrigeration power		0,178
	Climat class	4	
<u>SOUND LEVEL</u>			< 65,00 db
<u>CERTIFICATES</u>	SGS-2103-0906-1		
<u>INSTALLATION - CONNECTIONS</u>	Ø		
	► ELECTRICITY	SI	

DESCRIPTION

OVER COUNTER DISPLAY CASES, VTP-139 RP

SPECIFICATIONS

High quality austenitic stainless steel inner tray.
 Anodized aluminium outside panels. Glass with PVC on the sides.
 Curved glass cover (one piece) or flat cover (two pieces) and glass sliding doors.
 40 kg/m3 injected polyurethane isolation. CFC free.
 It can fit GN -1/3, 40 mm deep containers. The containers are included in the standard equipment.
 The cooling unit may be inside or outside the room and can be placed at a distance from the cabinet.
 Remote cooling unit versions include the cooling unit as part of the standard equipment. Its dimensions are 310 x 360 x 240 mm and the maximum distance to the cabinet is 1.5 m.
 Cold plate with copper tube evaporator.
 Emergency waste water drainage.
 Electronic thermostat for temperature control.
 Shielded inner lighting system.
 Lighted power switch.
 Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Glass type: Flat
 Containers capacity: 7*GN 1/3
 Cooling unit type: Remote
 Electricity consumption: 183 W
 Coolant: R-134a
 Dimensions: 1.380x415x278 mm



Catalogue :
OTHER REFRIGERATION

Chapter :
DISPLAY TRAYS

Article :
VTP-139 RP Remote Flat Negro 230V 1N 50H

Code :
19005240

SCHEMA - DIMENSIONS

